



RM Grid magnets

Separation systems for various industries



Bakker Magnetics

Always ahead.

Datasheet Bakker Magnetics

RM Grid magnets

version 1.1

- Execution : Grid magnet type RM
Sturdy construction
Permanent magnetic
- Housing : Stainless steel 1.4301
- Surface treatment : Blasted
- Magnetic part : Permanent ceramic magnets quality BM7 or
Permanent Neodymium magnets quality BM35

Under normal circumstances Bakker Magnetics provides a life-time guarantee on the applied ceramic magnets.

Also available:

- Easy clean version (RM/EC)
- Automatic (cleaning) version (RM/A)
- Execution with AlNiCo magnets suitable for high temperatures

Standard ceramic version (RM) Square

Article number	A	B	# Bars	Weight (kg)
25.150	100	100	2	1
25.151	150	150	3	2
25.152	200	200	4	3
25.153	250	250	5	5
25.154	300	300	6	6
25.155	400	400	8	9
25.156	500	500	10	15
25.157	600	600	12	21

Standard ceramic version (RM) Round

Article number	A	# Bars	Weight (kg)
25.100	Ø 100	3	0,5
25.101	Ø 150	3	1,5
25.102	Ø 200	4	3
25.103	Ø 250	5	4
25.104	Ø 300	6	5
25.105	Ø 350	7	7
25.106	Ø 400	8	8
25.107	Ø 450	9	10
25.108	Ø 500	10	13
25.109	Ø 550	11	16
25.110	Ø 600	12	20

Sizes and dimensions (in mm) as shown on the drawing on the last page.



Bakker Magnetics

Always ahead.

For more information or questions please contact us:

Bakker Magnetics

Sciencepark Eindhoven 5502
5692 EL Son, The Netherlands

Division: Magnetic Separation Technology

Phone : +31 (0) 40 2 678 840

Mail : mst@bakkermagnetics.com

Dimensions and shape of the magnet, in combination with required manufacturing processes, may cause the magnetic and physical characteristics to vary from typical values. Therefore, all data presented in this document are for general reference only and should not be relied upon to represent standard characteristics, nor are they guaranteed upon use. Bakker Magnetics reserves the right to change information in this document, including magnet performance standards, specifications, and characteristics without notice.



Always ahead.

